



FCQHG-F / RZQG

Roundflow Cassette

Hi Efficiency – Seasonal Smart



RZQG125L8V1

Outdoor Unit

RZQG71	H x W x D	990 x 940 x 320mm
RZQG100/125/140	H x W x D	1430 x 940 x 320mm

Accessories

Self cleaning deco-panel (BRCQ140DG)
White louvred deco-panel (BRCQ140DW)
Presence sensor (BRYQ140A)
Fresh air intake kit (KDDQS5B140)

Daikin's unique 360° Roundflow cassette, re-engineered. The Hi-COP Roundflow cassette exceeds Energy Related Products Directive minimum efficiency standards for Seasonal Efficiency, combining industry leading efficiencies with functionality to suit office and retail applications.

The Roundflow cassette has 23 different air flow settings to ensure optimum airflow and temperature distribution, while the presence and floor sensors can detect people and adjust temperature and airflow direction to ensure comfort and efficiency.

Energy savings can be made using the remote controller which gives control over set-point ranges and day-to-day use of controls. The controller also gives a kWh indication of the power consumed by the cassette and outdoor unit so you can monitor your energy usage.

Energy efficiencies can be improved by utilising the selectable evaporating and condensing temperature option, making the Hi-COP cassette the ideal solution for energy conscious building managers.



FEATURES

- Programmable air discharge outlets via remote control
- Selectable evaporating and condensing temperatures
- D3 connection as standard
- Presence sensor (BRYQ140A)
- Self-cleaning decoration panel (BYCQ140DG)

BENEFITS

- Room configurations can be changed without re-positioning cassette
- Improves energy efficiency of the 'out of the box' system by 20%, saving money on running costs and can help reduce cold draughts
- Allows integration of split system into Daikin building management systems
- Controlling temperature set point based on occupancy can reduce running costs by up to 27%. Directing air-flow away from occupants ensures improved comfort levels
- Automatic cleaning of air-filter can save up to 30% in running costs

Indoor Units			Single Phase				3 Phase				
			FCQHG71F	FCQHG100F	FCQHG125F	FCQHG140F	FCQHG71F	FCQHG100F	FCQHG125F	FCQHG140F	
Cooling Capacity	Nominal	kW	6.8	9.5	12	13.4	6.8	9.5	12	13.4	
	UK Total	kW	7.76	10.8	13.6	14.9	7.76	10.8	13.6	14.9	
	UK Sensible	kW	5.32	7.44	9.3	10.25	5.32	7.44	9.3	10.25	
Heating Capacity	Nominal	kW	7.5	10.8	13.5	15.5	7.5	10.8	13.5	15.5	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A++				A++				
		Pdesign	kW	6.8	9.5	12.0	-	6.8	9.5	12.0	-
		SEER		7.00	7.00	6.61	-	7.00	7.00	6.61	-
	Heating (Average climate)	Annual energy consumption	kWh	340	475	635	-	340	475	635	-
		Energy label		A+				A++			
		Pdesign	kW	7.6	11.3	14.1	-	7.6	11.3	14.1	-
Nominal efficiency (cooling at 35°/27° nominal load, heating at 7°/20° nominal load)	EER	COP	4.09	4.42	4.00	3.35	4.09	4.42	4.00	3.35	
		Annual energy consumption	kWh	830	1,075	1,500	2,000	830	1,075	1,500	2,000
		Energy label	Cooling/Heating	A/A				A/A			
Nominal Power Input	Cooling / Heating	kW	1.66 / 1.56	2.15 / 2.16	3 / 3.07	4 / 3.77	1.66 / 1.56	2.15 / 2.16	3 / 3.07	4 / 3.77	
Dimensions (with deco-panel)	Height x Width x Depth	mm	288(348) x 840 (950) x 840 (950)				288(348) x 840 (950) x 840 (950)				
Weight (with deco-panel)		kg	25 (30.5)	26 (31.4)			25 (30.5)	26 (31.4)	26 (31.4)	26 (31.4)	
Air Flow Rate	High / Low	m³/min	21.2 / 12.2	32.3 / 19	33.5 / 19.9	33.2 / 21.1	21.2 / 12.2	32.3 / 19	33.5 / 19.9	33.2 / 21.1	
Sound Power	High	dB(A)	53	61	61	61	53	61	61	61	
Sound Pressure	High / Low	dB(A)	36 / 29	44 / 33	45 / 35	45 / 37	36 / 29	44 / 33	45 / 35	45 / 37	
Refrigerant	Type		R410A				R410A				
Power Supply			From outdoor unit				From outdoor unit				
Controller			BRC1E52A wired				BRC1E52A wired				

Outdoor Unit			RZQG71L8V1	RZQG100L8V1	RZQG125L8V1	RZQG140L7V1	RZQG71L8Y1	RZQG100L8Y1	RZQG125L8Y1	RZQG140LY1
Dimensions	Height x Width x Depth	mm	990 x 940 x 320	1430 x 940 x 320			990 x 940 x 320	1430 x 940 x 320		
Weight		kg	78	99			80	101		
Operation Range	Cooling Min~Max	°CDB	-15°C to +50°C				-15°C to +50°C			
	Heating Min~Max	°CWB	-20°C to +15.5°C				-20°C to +15.5°C			
Sound Power	High	dB(A)	64	66	67	69	64	66	67	69
Sound Pressure	Nominal	dB(A)	48	50	51	52	48	50	51	52
Refrigerant	Type		R410A				R410A			
Power Supply			1~ / 50Hz / 220 - 240v				3~ / 50Hz / 400v			
Piping connections	Liquid (OD)/Gas	inches	3/8 / 5/8				3/8 / 5/8			
Piping Length (Maximum)		m	50	75			50	75		
Max Installation Height Difference		m	30				30			



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin products are distributed by: