Standard Series

SRK-ZMP

Wall Mounted type

R410A

NEW

SRK25ZMP-S, SRK35ZMP-S
SRK45ZMP-S

Refrigerant pipe length



SRK25ZMP-S
SRK35ZMP-S



SRK45ZMP-S

Standard equipment

SRC25ZMP-S
SRC35ZMP-S

SRC45ZMP-S

FUNCTION

Comfortable Functions

Self Clean Operation | Fuzzy | Auto | HI POWER

Comfortable Air Flow Functions

Auto Flap | Memory | UP/DOWN

Convenient & Economy Functions

Economy | DRY | OFF Timer | Sleep | On 24h Timer Off | On Timer

Maintenance & Prevention Functions

MC | Self Diagnostic | Detachable

Others

Back-up Switch | Auto Restart | Luminous

SPECIFICATIONS

Indoor unit				SRK25ZMP-S	SRK35ZMP-S	SRK45ZMP-S
Outdoor unit				SRC25ZMP-S	SRC35ZMP-S	SRC45ZMP-S
Power source				1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min~Max)			kW	2.5(0.9~2.8)	3.2(0.9~3.5)	4.5(0.9~4.8)
Nominal heating capacity (Min~Max)			kW	2.8(0.8~3.9)	3.6(0.9~4.3)	5.0(0.8~5.8)
Power consumption		Cooling/Heating	kW	0.78 / 0.755	0.995 / 0.995	1.495 / 1.385
EER/COP		Cooling/Heating		3.21/3.71	3.22 / 3.62	3.01 / 3.61
Inrush current		220/230/240 V	A	3.9 / 3.8 / 3.6	4.9 / 4.7 / 4.5	7.0 / 6.7 / 6.4
Max. running current				9	9	14
*Sound power level	Indoor	Cooling/Heating	dB(A)	59 / 58	60 / 58	60 / 64
	Outdoor	Cooling/Heating		60 / 59	60 / 60	65 / 65
*Sound pressure level	Indoor	Cooling (Hi/Me/Lo)		45 / 34 / 23	47 / 36 / 23	46 / 40 / 25
		Heating (Hi/Me/Lo)		43 / 34 / 26	44 / 36 / 28	48 / 43 / 32
	Outdoor	Cooling/Heating		47 / 45	49 / 48	52 / 53
Air flow	Indoor	Cooling (Hi/Me/Lo)	m^3/min	10.1 / 7.3 / 4.2	9.5 / 6.8 / 4.2	9.0 / 7.2 / 3.8
		Heating (Hi/Me/Lo)		9.5 / 7.3 / 5.2	9.6 / 7.4 / 5.5	12.0 / 9.2 / 6.2
	Outdoor	Cooling/Heating		26.0 / 19.7	25.4 / 20.5	35.5 / 33.5
Exterior dimensions	Indoor	HeightxWidthxDepth	mm	262 x 769 x 210		
	Outdoor			540 x 645(+57) x 275		595 x 780(+62) x 290
Net weight	Indoor / Outdoor		kg	6.9 / 25	7.2 / 27	7.6 / 40
Ref.piping size	Liquid/Gas		ø mm	6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length			m	Max. 15		Max. 25
Vertical height differences		Outdoor is higher/lower	m	Max. 10 / Max. 10		Max. 15 / Max. 15
Outdoor operating temperature range		Cooling	˚C	-15~46		
		Heating		-15~21		
Clean filter				–		

The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27˚CDB, 19˚CWB, and outdoor temp. of 35˚CDB. Heating: Indoor temp. of 20˚CDB, and outdoor temp. of 7˚CDB, 6˚CWB.
* Indicates the value in an anechoic chamber.During operation these values are somewhat higher due to ambient conditions.